

FRONTIER™ STRAW

EMERGENCY FILTER



USER MANUAL

Model Number 67005, 67109

EPA Est. No 71766-UT-001

FRONTIER™ STRAW

INTRODUCTION

Thank you for purchasing the Frontier Straw Filter. You have joined with over a hundred thousand users that rely on the Frontier Straw to protect them from crypto and Giardia, the leading causes of waterborne illness.

FEATURES

- Miraguard™ Antimicrobial* Technology
- Lightweight and compact
- BPA free, Lead Free, chemical free, and iodine free

CAUTIONARY STATEMENTS

- CAUTION - To avoid cross contamination: Do not handle filter or straw with wet hands that have been exposed to contaminated water. Do not submerge filter to the straw in contaminated water.
- CAUTION - Do not freeze filter or expose filter to extreme temperatures
- WARNING - Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

COMPONENTS




PARTS LIST

PART #	ITEM NAME
1 076707	Frontier Straw Filter
2 050113	Straw

PRODUCT INSTRUCTIONS

AS A STRAW FILTER



STEP 1

Attach the straw to the Frontier Emergency Filter.

STEP 2

Submerge the Frontier Emergency Filter in water source and sip through straw.

NOTE: To remove harmless carbon dust on initial use, draw water halfway up straw and discard water, then re-attach straw and drink normally.

Filter Storage

- Allow filter to air dry at room temperature for at least 48 hours prior to storing.
- Once dry, store filter and straw in pouch, store in a cool dry location. Do not store used filter in a sealed container.
- Do not freeze filter or expose filter to extreme temperatures.

TECHNICAL INFORMATION

LIMITED WARRANTY AND DISCLAIMER

Aquamira Technologies, Inc. warrants all product to be free from defects in workmanship and materials for one year from the date of purchase by the consumer, or for the duration of the imprinted shelf life. Filter clogging or normal wear is not a defect. If you are not satisfied with the performance of an Aquamira Technologies, Inc. product, Aquamira Technologies, Inc. will repair or replace the product.

Aquamira Technologies hereby excludes any expressed or implied warranties of fitness for a particular purpose. The following is made in lieu of any such warranties: The information and specifications supplied by Aquamira Technologies, Inc. are based on standard laboratory test conditions and are believed to be reliable, but Aquamira Technologies, Inc. does not guarantee that any result shown or claimed will be obtained. Before using any Aquamira product, the user shall determine the suitability and fitness of the products for their intended use. The effectiveness of Aquamira products may be limited by environmental or hygienic conditions, such as use with contaminated hands, recontamination after filtration or treatment, failure to maintain a sterile mouthpiece or downstream equipment, sharing with multiple users, exposure to extreme environmental conditions such as heat, freezing, severe shock such as drops or other impact that may damage the integrity of the filter, seals or connections etc. The user assumes all risks and liability in connection with its own tests and use. Aquamira Technologies, Inc. shall not be liable for any injury, loss or damage, direct or consequential, resulting out of or from the use, misuse, or inability to use Aquamira Technologies, Inc. products. inability to use Aquamira products.

FILTER CARTRIDGES

PARAMETER	BLU Line Filter
Service Life	30 Gal. (113 L)
Flow Rate	up to 450 ml/min
Operating Temperatures	35-120° F (1.6-49° C)
Operating Pressures	0-3 psi (0-0.211 kg f/cm ²)
Use Conditions	Use best water source available, quality of the source water may vary. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Pre-treatment with Aquamira Water Treatment Drops (67202) is recommend if source water is microbiologically unsafe or of unknown quality.

Removal

BLU LINE	PARASITE PROTECTION
Cyst Removal	≥99.95%
Chlorine, Chemical, Taste & Odor Removal	
MEETS OR EXCEEDS ANSI/NSF 42	

CERTIFICATIONS AND PATENTS



Certified by IAPMO R&T to NSF/ANSI 372 for lead free content. Meets US EPA Microbiological Purifier test standard for the reduction of cysts.

aquamira

917 West 600 North, Logan, UT 84321

ph: (877) 644-4650

www.aquamira.com

© Copyright 2016 Aquamira Technologies, Inc.

015228

aquamira